

# SAFRAN: An interpretable, rule-based link prediction method outperforming embedding models

Simon Ott<sup>1</sup>, Christian Meilicke<sup>2</sup>, Matthias Samwald<sup>1</sup>

<sup>1</sup> Institute of Artificial Intelligence and Decision Support, Medical University of Vienna, Austria

<sup>2</sup> Data and Web Science Research Group, University Mannheim, Germany


# Rule-based approach AnyBURL

## Advantages

- Efficient rule learning
- Explainable!

## Limitations

- Functional redundant rules
- Slow rule application




Meilicke, C. et al. (2019). Anytime Bottom-Up Rule Learning for Knowledge Graph Completion

$$\begin{aligned} \textit{speaks}(X, Y) &\leftarrow \textit{lives}(X, A_2), \textit{lang}(A_2, Y) \\ \textit{speaks}(X, d) &\leftarrow \textit{married}(X, A_2), \textit{born}(A_2, a) \end{aligned}$$

# SAFRAN

- Scalable and fast non-redundant rule application
- **Clustering of redundant rules**  
Elevating predictive performance
- **Scalability**  
Enables the application of symbolic rules to large scale KBs



# Results

Approach		FB15K-237			WN18RR			YAGO3-10				
		MRR	hits@1	hits@10	MRR	hits@1	hits@10	MRR	hits@1	hits@10		
Latent	RESCAL	★	.357	.263	.541	.468	.439	.521				
	TransE	★	.313	.221	.497	.227	.053	.526	¶	.501	.405	.673
	DistMult	★	.343	.250	.531	.452	.413	.531	¶	.501	.412	.661
	ComplEx	★	.348	.253	.534	.477	.438	.543	¶	<b>.576</b>	<b>.505</b>	<b>.704</b>
	ConvE	★	.339	.248	.521	.447	.411	.508	¶	.488	.399	.657
	RotatE	¶	.336	.238	.531	.475	.426	.574	¶	.498	.405	.670
	Tucker	¶	.352	.259	.536	.459	.430	.514	¶	.544	.465	.680
	HAKE	▽	.346	.250	<b>.542</b>	.497	.452	<b>.582</b>		.545	.462	.694
Interpretable	C-NN	△	.296	.222	.446	.469	.444	.519				
	DRUM	‡	<i>.343</i> <sup>†</sup>	<i>.255</i> <sup>†</sup>	<i>.516</i> <sup>†</sup>	<i>.486</i> <sup>†</sup>	<i>.425</i> <sup>†</sup>	<i>.586</i> <sup>†</sup>				
	Neural LP	◇	<i>.240</i> <sup>†</sup>		<i>.362</i> <sup>†</sup>	<i>.435</i> <sup>†</sup>	<i>.371</i> <sup>†</sup>	<i>.566</i> <sup>†</sup>				
	GPFL	◇	.322	.247	.504	.480	.449	.552				
	AMIE+	♣		.174	.409		.358	.388				
	RuleN	♣		.182	.420		.427	.536				
	RLvLR	‡	.240		.393							
		Maximum		.355	.270	.519	.494	.452	.572	.559	.487	.686
	AnyBURL	Noisy-OR		.342	.258	.502	.454	.399	.562	.524	.444	.672
	with	VS		.363	.277	.526	.497	.455	.572	.560	.489	.689
SAFRAN	NRNO * (grid)		.370	.287	.531	.501	.457	.581	.564	.492	.691	
	NRNO * (random)		<b>.389</b>	<b>.298</b>	.537	<b>.502</b>	<b>.459</b>	.578	.564	.491	.693	

This work received funding from  
netidee grant 5171 ('OpenBioLink').

